

Laszlo Corporation

TECHNICAL SPECIFICATION FOR PRODUCT

NAME: TRICHLOROETHYLENE
GRADE: TECHNICAL

Field of usage: TCE is used as a solvent in chemical industry, as extraction agent for fats and oils, in chemical laundries and for cold hot degreasing of metallic parts (excluding those of aluminium, magnesium and their alloys).

Technical quality conditions:

No.	Property	MU	Conditions for Admissibility	Analysis Method
1.	Aspect	-	Clear Liquid	ASTM D 3741/2004
2.	Color (Pt-Co Scale)	Unit Hazen	Max 15	SR ISO 2211/1994
3.	Relative Density	-	1.455 – 1.465	ASTM D 2111/2002
4.	Trichloroethylene	%	Min. 99	Gas Chromatography
5.	Water Content	PPM	Max 100	SR ISO 760/1994
6.	Free Chlorine Content	-	None	ASTM D 4755/2004
7.	Evaporation Residue	PPM	Max 50	ASTM D 2109/2006
8.	pH of aqueous extract	Unit pH	8 – 11	ASTM D 2110/2006
9.	Stabilization Package	-	Butylene Oxide	

PACKING:

STAINLESS STEEL DRUMS WITH SPECIAL GASKETS AND BUNGS.